



2019
EDITION

CAR REFINISHING

 **HELIOS** RESINS



HELIOS

RESINS,

HIGH-QUALITY

RESINS FOR

RELIABLE

COATING

SOLUTIONS.

CAR REFINISHING

EXCELLENT MECHANICAL
PROPERTIES, SUPERIOR
OUTDOOR DURABILITY, AND
OUTSTANDING APPEARANCE
ARE GUARANTEED.

GOLDEN RESINS

Helios Resins is a separate business unit of Helios, now part of Kansai Paint, one of the world's leading paint and coatings producers. Today, Helios Resins produces around 60,000 tons of liquid resins annually, including coating resins, composite resins, and polyester polyols for PU flexible foams. Our coating resin brands – DOMOPOL, DOMACRYL, DOMALKYD, DOMEMUL and DOMOPUR – have achieved a strong market position and are trusted for their quality and performance. We currently serve more than 50 countries worldwide.

QUALITY OF SERVICE

We are committed to providing a flexible and reliable service while satisfying our customers' specific requests. Helios Resins ensures the quality, stability and reproducibility of every delivery. Our extensive know-how, resulting from more than 100 years of experience, enables us to provide solutions to our customers' challenges. Helios Resins experts produce tailor-made resins for specific needs and offer support in developing customized applications.

DEVELOPED WITH ADVANCED TECHNOLOGIES

Our laboratories and production facilities are fully equipped with the most advanced technologies, which enables the development and production of resins. Our R&D has advanced skills as well as equipment for polyester and acrylic chemistry, including synthesis under pressure. We are constantly upgrading our production lines and increasing our production capacities to meet the highest demands of our customers. In 2018 we introduced a new reactor line for water-based resins.

OUR STRENGTHS

- FLEXIBILITY
- ON-TIME DELIVERY
- HIGH QUALITY

ACRYLIC SOLVENTBORNE 2K RESINS

RESIN	DELIVERY FORM	ACID VALUE on solid resin [mg KOH/g]	HYDROXYL VALUE on solid resin [mg KOH/g]
DOMACRYL 503	55 X / BA _c / nB	10 – 15	
DOMACRYL 568	60 X / MPA	max. 10	55 – 65
DOMACRYL 504	60 X / BA _c	max. 10	55 – 65
DOMACRYL 536	60 X	max. 10	75 – 100
DOMACRYL 5705	60 X	5 – 10	85 – 105
DOMACRYL 5130	70 BA _c	6 – 10	90 – 110
DOMACRYL 521	60 X	max. 10	100 – 120
DOMACRYL 5501	74 BA _c	8 – 10	100 – 120
DOMACRYL 5251	70 BA _c	max. 10	100 – 120
DOMACRYL 5210	75 BA _c	7 – 11	110 – 130
DOMACRYL 547	60 X / SA / BA _c	10 – 16	110 – 130
DOMACRYL 5117	70 BA _c	8 – 12	120 – 140
DOMACRYL 5475	65 X / BA _c	5 – 12	120 – 140
DOMACRYL 5187	70 BA _c	max. 15	130 – 145
DOMACRYL 5108	80 BA _c	max. 16	130 – 150
DOMACRYL 5155	60 X / SA / BA _c	max. 10	130 – 150
DOMACRYL 5481	75 BA _c	max. 12	130 – 150
DOMACRYL 549	70 X / BA _c	9 – 15	130 – 150
DOMACRYL 5485	75 BA _c	max. 12	135 – 155
DOMACRYL 5495	70 X / BA _c	5 – 13	135 – 155
DOMACRYL 5500	75 BA _c	8 – 12	140 – 160
DOMACRYL 5505	75 BA _c	max. 12	140 – 160
DOMACRYL 5506	75 BA _c	max. 12	140 – 160
DOMACRYL 522	60 X / MPA	18 – 25	140 – 160
DOMACRYL 522	60 X / SA / BA _c	max. 10	140 – 160
DOMACRYL 526	70 BA _c	max. 8	140 – 160
DOMACRYL 5415	70 BA _c	max. 12	140 – 160
DOMACRYL 544	60 X / SA / BA _c	max. 12	140 – 160
DOMACRYL 543	60 X / SA / BA _c	8 – 14	145 – 165
DOMACRYL 543	60 X / MPA	8 – 14	145 – 165
DOMACRYL 5150	75 BA _c	2 – 15	145 – 170

VISCOSITY 23 °C [mPa.s]	DESCRIPTION
1700 – 2600	Basecoat resin.
3000 – 5000	Universal resin.
5500 – 7500	Resin for very elastic basecoat and pigment paste. Good compatibility with other OH acrylic resins.
1300 – 2300	Standard resin for clear and top coats. Available also in BAc and SA.
3000 – 4000	Standard resin. Good adhesion, hardness, gloss and elasticity.
4000 – 6000	Broad compatibility with similar acrylic resins. Good balance between hardness and flexibility.
1400 – 1600	Standard high gloss resin. Good adhesion on different substrates.
3500 – 6500	Excellent mechanical properties and superior outdoor durability.
8000 – 12000	Good balance between hardness and flexibility, with good weather and chemical resistance.
5000 – 8500	High solid top and clear coats.
2500 – 3500	Rapid initial drying.
1000 – 1400	Very good lightfastness and good resistance to solvents.
3500 – 4500	Fast drying.
2800 – 4200	Broad compatibility with similar acrylic resins. Good balance between hardness and flexibility, with excellent mechanical properties and superior outdoor durability and solvent resistance.
4000 – 8000	Very high solid.
3000 – 4000	High abrasion resistance, high resistance to chemicals and water.
4500 – 6000	Excellent pigment wetting. CAB compatible.
2500 – 4000	Fast drying.
8000 – 12000	Excellent resistance and weather stability. CAB compatible.
1200 – 2400	Good balance between hardness and flexibility. Excellent mechanical properties and superior outdoor durability.
3500 – 10000	Very good balance between hardness and flexibility. Excellent mechanical properties and superior chemical resistance.
4000 – 7000	Excellent mechanical properties and superior outdoor durability.
3000 – 5000	Excellent mechanical properties and superior outdoor durability.
4000 – 5000	Very good gloss retention and superior outdoor durability.
4000 – 6000	Standard high-performance resin.
7000 – 11000	Standard high-performance resin.
3600 – 6000	Top performance resin.
3500 – 8000	Fast drying. Also for primers including plastics.
2300 – 2800	Standard high-performance resin.
2000 – 2500	Standard high-performance resin.
3500 – 6500	Excellent chemical and petrol resistance, good weathering and yellowing resistance.



ACRYLIC SOLVENTBORNE SPECIALITIES

RESIN	DELIVERY FORM	ACID VALUE on solid resin [mg KOH/g]	HYDROXYL VALUE on solid resin [mg KOH/g]
DOMACRYL 5245	75 BAc	max. 3	125 – 145
DOMACRYL 5451	50 BAc	max. 3	55 – 70
DOMACRYL 872	60 X	8 – 12	

ALKYD SOLVENTBORNE RESINS

RESIN	DELIVERY FORM	OIL LENGTH / OIL TYPE	ACID VALUE on solid resin [mg KOH/g]
DOMALKYD 1468	50 Solvent mix	46% Non-yellowing FA	max. 12
DOMALKYD 1482	55 W / X	48% Soyabean FA	max. 12
DOMALKYD 1526	55 W	52% Soyabean oil	max. 15

POLYESTER SOLVENTBORNE RESINS

RESIN	DELIVERY FORM	ACID VALUE on solid resin [mg KOH/g]	HYDROXYL VALUE on solid resin [mg KOH/g]
DOMOPOL 5193	70 X	max. 12	95 – 105
DOMOPOL 6028	78 BAc	20 – 25	220 – 250
DOMOPOL 6067	80 BAc	max. 2	130 – 160

ACRYLIC WATERBORNE RESINS

RESIN	DELIVERY FORM	ACID VALUE on solid resin [mg KOH/g]	HYDROXYL VALUE on solid resin [mg KOH/g]
DOMACRYL 0724	45 Wa / PnB / SA	24 – 30	125 – 145
DOMACRYL 0768	42 Wa / PnB	20 – 30	130 – 150
DOMACRYL 0795	41 Wa / PnB	24 – 30	155 – 175
DOMEMUL RA 9675	35 Wa	20 – 30	

APEO = Alkylphenol ethoxylate, BAc = Butyl acetate, CAB = Cellulose acetate butyrate, FA = Fatty acid, DTM = Direct-to-metal, MPA = Methoxy propyl acetate, nB =



VISCOSITY 23 °C [mPa.s]	DESCRIPTION	
2000 – 5000	Extremely fast drying and long pot-life. Superior mechanical properties and outdoor durability.	PATENT PENDING
4000 – 6000	Extremely fast drying fillers.	PATENT PENDING
10000 – 15000	Pigmented and transparent paints for plastic. Rapid drying and excellent toughness. Tg = 50 °C.	

VISCOSITY 23 °C [mPa.s]	DESCRIPTION
660 – 1000	Very fast surface and through-drying with high gloss and resistance to yellowing.
5000 – 7000	Standard resin with very good overall properties. Air and forced drying.
2000 – 3000	Pigment pastes for combination with medium oil air-drying alkyd resins with excellent weather resistance.

VISCOSITY 23 °C [mPa.s]	DESCRIPTION
2000 – 3000	Primer surfacers and metallic base coats.
8000 – 13000	Clear and pigmented top coats with high hardness and excellent solvent and chemical resistance.
1800 – 2600	Can be added to 2K PUR systems to improve their flexibility.

VISCOSITY 23 °C [mPa.s]	pH	DESCRIPTION
200 – 1000	7.0 – 8.0	Acrylic secondary dispersion. Standard resin for 2K PUR systems.
200 – 5000	8.0 – 9.0	Acrylic secondary dispersion. Standard resin for 2K PUR systems. High gloss, without aromatic co-solvent.
200 – 2000	7.0 – 8.0	Acrylic secondary dispersion. Top quality 2K PUR systems. Suitable for DTM.
50 – 1000	6.0 – 7.0	Acrylic APEO-free latex resin for effect pigmented coatings (metallic, pearlescent).

n-Butanol, PnB = Propylene glycol monobutyl ether, SA = Aromatic solvent 100, W = White spirit, Wa = Water, X = Xylene.



ISO 9001
ISO 14001

BUREAU VERITAS
Certification



Helios TBLUS d.o.o.
Količevo 65, 1230 Domžale, Slovenia

T +386 1 722 40 71
T +386 1 722 43 94
info@resinshelios.com
www.resinshelios.com

Part of  **KANSAI**
PAINT