

Product code: 481171

DOMACRYL 0707 43 Wa/DPM

Secondary Acrylic Dispersion

Specification:

Property	Range	Method / According to standard
Non-volatile matter	42 - 44%	MH1155 / ISO 3251
Acid value on solid resin	30 - 40 mg KOH/g	MH1051 / ISO 2114
Viscosity, 23 °C	100 - 3000 mPa·s	MH1007 / ISO 3219
pH	8 - 9	MH1040 / ISO 976

Typical properties:

Property	Value
Cosolvent	4.2% DPM
Appearance	Bluish milky white
Density	1.1 kg/L
Hydroxyl content on solid	3.3%
Neutralisation agent	2.5% Dimethylethanolamine, as salt

Applications:

Domacryl 0707 43 Wa/DPM is intended to be used as polyol component in STOVING aqueous clear- and top- coats for transport & ACE and general industry.

Storage:

The resin should be stored indoors in its original, unopened and undamaged container in a dry place at storage temperatures between 5 °C and 35 °C, for up to 12 months. Protect from freezing and avoid exposure to direct sunlight.

Note: The information contained herein is provided in good faith and is to the best of our knowledge accurate, but we assume no liability for its accuracy or completeness. Therefore, the buyer is advised to determine the suitability of this product for the intended use. We retain the right to make any changes according to technological progress or further developments. For safety information please refer to the current Material Safety Data Sheet.

Edition: July 2019

Helios TBLUS, d.o.o. | Količevo 65, 1230 Domžale, Slovenia | T +386 1 722 40 00, F +386 1 722 43 10
info@resinshelios.com | www.resinshelios.com
Member of HELIOS. Part of KANSAI PAINT.