

Product code: 448845

DOMALKYD 2755 100% LV

Alkyd Resin Based on Linseed Oil

Specification:

Property	Range	Method / According to standard
Non-volatile matter	min. 98%	MH1155 / ISO 3251
Acid value on solid resin	max. 15 mg KOH/g	MH1051 / ISO 2114
Viscosity, 23 °C	2000 - 3000 mPa·s	MH1007 / ISO 3219
Colour	max. 10 Gardner	MH1124 / ISO 4630

Typical properties:

Property	Value
Appearance	clear to opaque
Oil content	80%

Solubility:

Soluble in all usual solvents.

Compatibility:

Compatible with natural and polymerized oils, medium and long oil alkyds and colophonium modified maleic resins.

Applications:

Domalkyd 2755 100% LV is a low viscosity drying alkyd resin for production of high solid paint systems, low VOC.

Storage:

The resin should be stored indoors in its original, unopened and undamaged container in a dry place at storage temperatures below 35 °C, for up to 24 months. Exposure to direct sunlight should be avoided.

Note: The information contained herein is provided in good faith and is to the best of our knowledge accurate, but we assume no liability for its accuracy or completeness. Therefore, the buyer is advised to determine the suitability of this product for the intended use. We retain the right to make any changes according to technological progress or further developments. For safety information please refer to the current Material Safety Data Sheet.

Edition: June 2023

Helios TBLUS, d.o.o. | Količevo 65, 1230 Domžale, Slovenia | T +386 1 722 40 00
info@resinshelios.com | www.resinshelios.com
Part of KANSAI PAINT.