

Product code: 481743

DOMEMUL AA 9673

APEO-free Self-crosslinking Acrylic Emulsion

Specification:

Property	Range	Method / According to standard
Non-volatile matter	40 - 42%	MH1155 / ISO 3251
Viscosity, 23 °C	20 - 350 mPa·s	MH1007 / ISO 3219
pH	7.5 - 9	MH1040 / ISO 976

Typical properties:

Property	Value
Appearance	Brownish
Density	1.0 kg/L
MFFT	7 °C

Applications:

- » Designed for industrial and decorative waterborne wood coatings, interior and exterior.
- » Recommended for furniture, joinery, decorative application, non-yellowing, with good wetting and alkaline resistance, low foaming, fast drying and very good blocking resistance.

Storage:

The resin should be stored indoors in its original, unopened and undamaged container in a dry place at storage temperatures between 5 °C and 35 °C, for up to 6 months. Protect from freezing and avoid direct sunlight.

Note: The information contained herein is provided in good faith and is to the best of our knowledge accurate, but we assume no liability for its accuracy or completeness. Therefore, the buyer is advised to determine the suitability of this product for the intended use. We retain the right to make any changes according to technological progress or further developments. For safety information please refer to the current Material Safety Data Sheet.

Edition: June 2023

Helios TBLUS, d.o.o. | Količevo 65, 1230 Domžale, Slovenia | T +386 1 722 40 00
info@resinshelios.com | www.resinshelios.com
Part of KANSAI PAINT.