

Product code: 481744

## DOMEMUL OHA 9200

### OH-functional Styrene-acrylic Emulsion

**Specification:**

Property	Range	Method / According to standard
Non-volatile matter	44 - 46%	MH1155 / ISO 3251
Viscosity, 23 °C	20 - 600 mPa·s	MH1007 / ISO 3219
pH	7.5 - 9	MH1040 / ISO 976

**Typical properties:**

Property	Value
Solvent	Water
Appearance	Milky white
Density	1.0 kg/L
Hydroxyl content on solid	2,7%
Tg	53 °C

**Applications:**

- » Used for the preparation of industrial waterborne 2K paints for metal, plastic, wood...
- » Recommended for application for high gloss clear coats and as well as pigmented top coats, with good adhesion to metal, good humidity resistance and good gloss in coating.
- » The material does not contain solvents (VOC-free).

**Storage:**

The resin should be stored indoors in its original, unopened and undamaged container in a dry place at storage temperatures between 5 °C and 35 °C, for up to 6 months. Protect from freezing and avoid direct sunlight.

**Note:** The information contained herein is provided in good faith and is to the best of our knowledge accurate, but we assume no liability for its accuracy or completeness. Therefore, the buyer is advised to determine the suitability of this product for the intended use. We retain the right to make any changes according to technological progress or further developments. For safety information please refer to the current Material Safety Data Sheet.

Edition: July 2019

Helios TBLUS, d.o.o. | Količevo 65, 1230 Domžale, Slovenia | T +386 1 722 40 00, F +386 1 722 43 10  
info@resinshelios.com | [www.resinshelios.com](http://www.resinshelios.com)  
Member of HELIOS. Part of KANSAI PAINT.