

COLPOLY 7100

Unsaturated Polyester Resin

Description:

Colpoly 7100 is a low viscous, monomer free unsaturated polyester resin based on a special composition.

Application:

Colpoly 7100 is recommended as a grinding medium for pigment concentrates.

Features and benefits:

- » Good pigment wetting properties.
- » Excellent storage stability.

Physical characteristics of the liquid resin:

Property	Range	Method / According to standard
Appearance	Clear	
Acid value	5 - 15 mg KOH/g	MH1051 / ISO 2114
Non-volatile matter	95 - 99%	MH1155 / ISO 3251
Viscosity, 25 °C	300 - 400 mPa·s	MH1009 / ISO 3219
Colour	max. 150 APHA	MH1125 / ISO 6271
Shelf life at 25 °C in darkness	12 months	

Handling and safety precautions:

Colpoly 7100 should be stored indoors in a dry place at temperatures between 5 - 30 °C. For further details, please see the relevant Safety Data Sheet.

Note: The information contained herein is provided in good faith and is to the best of our knowledge accurate, but we assume no liability for its accuracy or completeness. Therefore, the buyer is advised to determine the suitability of this product for the intended use. We retain the right to make any changes according to technological progress or further developments. For safety information please refer to the current Material Safety Data Sheet.

Edition: July 2023